

Step-by-Step Instructions

(PRINT this set of instructions to follow every time you refill your cartridge)

Lexmark Cartridge 18C1530 #3 Black Pigment cartridge



Items needed: gloves, #6 refill station, hand-drill, black pigment ink, paper towels, review hints & tips and check list. Do not plug fill hole.

Syringe: Attach needle tip (located inside station # 4) to the syringe tightly. Unscrew lid on ink bottle. Puncture silver seal with needle tip making a small hole in the center of seal. Using the correct color pull the correct amount of ink into the syringe. Rinse syringe and needle tip after every use and before using syringe with another color. Rinse syringe and needle tip with water until the water runs clear.

1.) Place cartridge in Station #6 with copper circuits facing to the left and the plastic feet inside the bottom of the station to your right. Place the lid on the cartridge with single hole on the left and double holes on the right. Make sure lid snaps down over top of cartridge.

2.) Insert the drill into the single hole on the left side of the lid. Drill a hole and make sure the drill goes thru the lid and deep into the inkjet cartridge below. Remove the lid from cartridge. Leave cartridge in refill station.

3.) Insert the black pigment ink using the syringe deep inside the fill-hole. Slowly dispense 15 ml of the black pigment ink into fill-hole. **As you inject the ink withdraw and re-insert the syringe at different angles in order to expose the whole sponge to the ink.** If ink begins to "bubble" out of the fill-hole, remove the bottle tip. Bubbling occurs when a cartridge is either over-filled or if the ink is being inserted too quickly. Wait several minutes and then try to slowly insert more ink. If ink begins to bubble out the fill-hole or leak from the printhead, you have plenty of ink in the cartridge.

4.) After refilling, remove cartridge from refill station. Place cartridge upright on folded paper towels with the printhead facing down toward the paper towel. Do not let the printhead touch the paper towel. It maybe necessary to tilt the cartridge slightly so printhead is not in contact with paper towel. Let cartridge sit for approximately 20 minutes after refilling before putting cartridge back into printer.

For best results, let cartridge sit for 8 hours after refilling so the ink can saturate the entire sponge.

5.) Do not plug fill-hole. If fill-holes are plugged, a slight vacuum is created. This can result in interrupted print or no print. If you place the label or piece of tape over the top of the refilled cartridge & cover the holes, please use the drill to poke a hole through the label or tape of one hole. One of the three holes needs to remain completely open.

6.) Check the ink flow by gently pressing a dry paper towel against the printhead. You should see a line or dot of Black ink. If not, gently press a warm, wet paper towel against the printhead until the black is visible.

7.) When black is visible on paper towel, place cartridge back into the printer and run 1 to 2 print tests. [Or Print 3 pages using:](#)

http://www.refills4you.com/support/black_print_test.html Black ink test
http://www.refills4you.com/support/color_print_test.html Color ink Test

PLEASE NOTE: If you have tried printing with your cartridge completely out of ink, you may have damaged the printhead. Inkjet printers work by heating a resistor inside the printhead which heats the ink before it is sprayed onto the paper. If there is no ink to keep the resistors cool, you stand the chance of frying them. In your worst case you will need to buy a new cartridge.

Note: The cartridge will print just like a new one. Even though the cartridge prints well, the ink level gauge will not read full after a refill.

AccuBrite, Inc. is not affiliated with the listed printer manufacturers or their subsidiaries. The use by AccuBrite, Inc. does not imply endorsement by or association with the brand name owners. The listed manufacturers, printers and cartridges are used only for the purpose of showing the compatibility of this AccuBrite, Inc. product. All other trademarks, brand names and logos referenced in or on this product are the property of their respective owners. This material is protected by the copyright laws of the United States and other countries. It is illegal to reproduce these instructions. It may not be reproduced, distributed, or altered in any fashion by any entity (either internal or external to AccuBrite), except in accordance with applicable agreements or contracts of licensing, without the express written consent of AccuBrite, Inc.

Copyright © AccuBrite, Inc. 2003-2008. All rights reserved