

Step-by-Step Instructions

(PRINT this set of instructions to follow every time you refill your cartridge)

Sharp UX-C70B



Items needed: gloves, black ink, drill, #4 black cradle, paper towels, review hints & tips and check list. Do not plug fill holes.

Syringe: Attach needle tip to the syringe tightly. Unscrew lid on ink bottle. Using the correct color pull the correct amount of ink into the syringe. Rinse syringe and needle tip after every use and before using syringe with another color. Rinse syringe and needle tip with water until the water runs clear.

Sharp UX-22BC Black Cartridge and others from Lexmark, Compaq, Xerox, and others

- Compaq 337709-001 Black Cartridge
- Compaq 33714-001 Black Cartridge
- Lexmark 12A1970 Black Cartridge
- Xerox 8R7881 Black Cartridge
- Sharp UX-22BC
- Sharp UX-C70B

The ink in this cartridge is retained because the cartridge has an internal sponge.

1. Make a hole in the top of the cartridge using the 1/16" thumb drill provided in parts pack located inside station # 4 (Do not remove the top.)
2. Release thru the needle tip 15 ml. of ink, insert the needle into the vent hole and push down into the center of the cartridge. Slowly inject up to 15ml. of black ink into the cartridge.
3. Set above a paper towel for half an hour as a drip precaution. Expect a few drips. Do not allow the cartridge to touch the paper towel at this point, since the towel will draw out the ink.
4. To test black printing, replace the cartridge and run 1 - 3 cleaning cycles as per printer instructions. Or print 2 pages at this test site <http://www.inkonline.net/support/blackinktest>
[Black ink test](#)

Cartridges should be refilled immediately and before they are empty.

For best results, leave cartridge in printer for 8 hours after refilling so the ink can saturate the entire sponge.

Copyright © AccuBrite, Inc. 2005-2010. All rights reserved